

Current ratings - IEC non regenerative

See the current ratings including several standard duty cycles for the DCS800 with 50 Hz and 60 Hz supplies below. The current ratings are based on an ambient temperature of maximum 40°C and an elevation of maximum 1000 m above mean sea level:

Unit type	I _{DC I}	I _{DC II}		I _{DC III}		I _{DC IV}		Size	Internal field current
2-Q converters	contin- ous	100 % 15 min	150 % 60 s	100 % 15 min	150 % 120 s	100 % 15 min	200 % 10 s		
400 V / 500 V / 525 V	[A]	[A]		[A]		[A]			
DCS800-S01-0020-04/05**	20	18	27	18	27	18	36	D1	6 A
DCS800-S01-0045-04/05**	45	40	60	37	56	38	76		
DCS800-S01-0065-04/05**	65	54	81	52	78	55	110		
DCS800-S01-0090-04/05**	90	78	117	72	108	66	132		
DCS800-S01-0125-04/05	125	104	156	100	150	94	188		
DCS800-S01-0180-04/05**	180	148	222	144	216	124	248	D2	15 A
DCS800-S01-0230-04/05	230	200	300	188	282	178	356		
DCS800-S01-0315-04/05**	315	264	396	250	375	230	460	D3	20 A
DCS800-S01-0405-04/05**	405	320	480	310	465	308	616		
DCS800-S01-0470-04/05	470	359	539	347	521	321	642		
DCS800-S01-0610-04/05**	610	490	735	482	723	454	908	D4	25 A
DCS800-S01-0740-04/05	740	596	894	578	867	538	1076		
DCS800-S01-0900-04/05	900	700	1050	670	1005	620	1240		
DCS800-S01-1190-04/05	1190 ①	860	1290	835	1253	745	1490	D4+	25 A * +S164
DCS800-S01-1200-04/05	1200	888	1332	872	1308	764	1528	D5	
DCS800-S01-1500-04/05	1500	1200	1800	1156	1734	1104	2208		
DCS800-S01-2000-04/05	2000	1479	2219	1421	2132	1361	2722		
DCS800-S01-2050-05	2050	1550	2325	1480	2220	1450	2900	D6	-
DCS800-S01-2500-04/05	2500	1980	2970	1880	2820	1920	3840		
DCS800-S01-3000-04/05	3000	2350	3525	2220	3330	2280	4560		
DCS800-S01-3300-04/05	3300	2416	3624	2300	3450	2277	4554	D7	-
DCS800-S01-4000-04/05	4000	2977	4466	2855	4283	2795	5590		
DCS800-S01-5200-04/05	5200	3800	5700	3669	5504	3733	7466		
600 V / 690 V									
DCS800-S01-0290-06	290	240	360	225	337	205	410	D3	-
DCS800-S01-0590-06	590	470	705	472	708	434	868	D4	-
DCS800-S01-0900-06/07	900	684	1026	670	1005	594	1188	D5	25 A * +S164
DCS800-S01-1500-06/07	1500	1200	1800	1104	1656	1104	2208		
DCS800-S01-2000-06/07	2000	1479	2219	1421	2132	1361	2722		
DCS800-S01-2050-06/07	2050	1520	2280	1450	2175	1430	2860	D6	-
DCS800-S01-2500-06/07	2500	1940	2910	1840	2760	1880	3760		
DCS800-S01-3000-06/07	3000	2530	3795	2410	3615	2430	4860		
DCS800-S01-3300-06/07	3300	2416	3624	2300	3450	2277	4554	D7	-
DCS800-S01-4000-06/07	4000	3036	4554	2900	4350	2950	5900		
DCS800-S01-4800-06/07	4800	3734	5601	3608	5412	3700	7400		
800 V									
DCS800-S01-1900-08	1900	1500	2250	1430	2145	1400	2800	D6	-
DCS800-S01-2500-08	2500	1920	2880	1820	2730	1860	3720		
DCS800-S01-3000-08	3000	2500	3750	2400	3600	2400	4800		
DCS800-S01-3300-08	3300	2655	3983	2540	3810	2485	4970	D7	-
DCS800-S01-4000-08	4000	3036	4554	2889	4334	2933	5866		
DCS800-S01-4800-08	4800	3734	5601	3608	5412	3673	7346		
990 V									
DCS800-S01-2050-10	2050	1577	2366	1500	2250	1471	2942	D7	-
DCS800-S01-2600-10	2600	2000	3000	1900	2850	1922	3844		
DCS800-S01-3300-10	3300	2551	3827	2428	3642	2458	4916		
DCS800-S01-4000-10	4000	2975	4463	2878	4317	2918	5836		
1190 V		Data on request							

* as option

** The 525 V version can be used as large field exciter. Do not forget the SDCS-DSL-4 (+S199).

A 10 % current de-rating is strongly recommended.

Note:

AC current $I_{AC} = 0.82 \cdot I_{DC}$

① 1190 A_{DC} for 35°C and 1140 A_{DC} for 40°C ambient temperature

Current ratings - IEC regenerative

Unit type	I _{DC I}	I _{DC II}		I _{DC III}		I _{DC IV}		Size	Internal field current
4-Q converters	continuous	100 % 15 min	150 % 60 s	100 % 15 min	150 % 120 s	100 % 15 min	200 % 10 s		
400 V / 525 V	[A]	[A]		[A]		[A]			
DCS800-S02-0025-04/05**	25	23	35	22	33	21	42	D1	6 A
DCS800-S02-0050-04/05**	50	45	68	43	65	38	76		
DCS800-S02-0075-04/05**	75	66	99	64	96	57	114		
DCS800-S02-0100-04/05**	100	78	117	75	113	67	134		
DCS800-S02-0140-04/05	140	110	165	105	158	99	198		
DCS800-S02-0200-04/05**	200	152	228	148	222	126	252	D2	15 A
DCS800-S02-0260-04/05	260	214	321	206	309	184	368		
DCS800-S02-0350-04/05**	350	286	429	276	414	265	530	D3	20 A
DCS800-S02-0450-04/05**	450	360	540	346	519	315	630		
DCS800-S02-0520-04/05	520	398	597	385	578	356	712		
DCS800-S02-0680-04/05**	680	544	816	538	807	492	984	D4	25 A
DCS800-S02-0820-04/05	820	664	996	648	972	598	1196		
DCS800-S02-1000-04/05	1000	766	1149	736	1104	675	1350		
DCS800-S02-1190-04/05	1190 ^①	860	1290	835	1253	745	1490	D4+	25 A * +S164
DCS800-S02-1200-04/05	1200	888	1332	872	1308	764	1528	D5	
DCS800-S02-1500-04/05	1500	1200	1800	1156	1734	1104	2208		
DCS800-S02-2000-04/05	2000	1479	2219	1421	2132	1361	2722		
DCS800-S02-2050-05	2050	1550	2325	1480	2220	1450	2900	D6	-
DCS800-S02-2500-04/05	2500	2000	3000	1930	2895	1790	3580		
DCS800-S02-3000-04/05	3000	2330	3495	2250	3375	2080	4160		
DCS800-S02-3300-04/05	3300	2416	3624	2300	3450	2277	4554	D7	-
DCS800-S02-4000-04/05	4000	2977	4466	2855	4283	2795	5590		
DCS800-S02-5200-04/05	5200	3800	5700	3669	5504	3733	7466		
600 V / 690 V									
DCS800-S02-0320-06	320	256	384	246	369	235	470	D3	-
DCS800-S02-0650-06	650	514	771	508	762	462	924	D4	-
DCS800-S02-0900-06/07	900	684	1026	670	1005	594	1188	D5	25 A * +S164
DCS800-S02-1500-06/07	1500	1200	1800	1104	1656	1104	2208		
DCS800-S02-2050-06/07	2050	1520	2280	1450	2175	1430	2860	D6	-
DCS800-S02-2500-06/07	2500	1940	2910	1870	2805	1740	3480		
DCS800-S02-3000-06/07	3000	2270	3405	2190	3285	2030	4060		
DCS800-S02-3300-06/07	3300	2416	3624	2300	3450	2277	4554	D7	-
DCS800-S02-4000-06/07	4000	3036	4554	2900	4350	2950	5900		
DCS800-S02-4800-06/07	4800	3734	5601	3608	5412	3700	7400		
800 V									
DCS800-S02-1900-08	1900	1500	2250	1430	2145	1400	2800	D6	-
DCS800-S02-2500-08	2500	1910	2865	1850	2775	1710	3420		
DCS800-S02-3000-08	3000	2250	3375	2160	3240	2000	4000		
DCS800-S02-3300-08	3300	2655	3983	2540	3810	2485	4970	D7	-
DCS800-S02-4000-08	4000	3036	4554	2889	4334	2933	5866		
DCS800-S02-4800-08	4800	3734	5601	3608	5412	3673	7346		
990 V									
DCS800-S02-2050-10	2050	1577	2366	1500	2250	1471	2942	D7	-
DCS800-S02-2600-10	2600	2000	3000	1900	2850	1922	3844		
DCS800-S02-3300-10	3300	2551	3827	2428	3642	2458	4916		
DCS800-S02-4000-10	4000	2975	4463	2878	4317	2918	5836		
1190 V	Data on request								

* as option ** The 525 V version can be used as large field exciter. Do not forget the SDCS-DSL-4 (+S199).
A 10 % current de-rating is strongly recommended.

Note: AC current $I_{AC} = 0.82 \cdot I_{DC}$

Note 1: The ratings apply at ambient temperature of 40°C (104°F). For lower temperatures the D5, D6, D7 ratings are higher (except I_{max}).

Note 2: Use DriveSize for detailed dimensioning in case the ambient temperature is below 40°C (104°F) or the drive is loaded cyclically.

① 1190 A_{DC} for 35°C and 1140 A_{DC} for 40°C ambient temperature

Standard duty cycles

